

31 Hedley Road St Albans Hertfordshire AL1 5JL **t:** +44 (0) 1727 830 151 **f:** +44 (0) 1727 855 993 **e:** info@camstage.com **w:** www.camstage.com


Auditoria Roller Screen
DENHAM
DATA SHEET

DOCUMENT REF: DS-12 Issue 8 June 2006

Technical Information for the Denham Electrical Roller Screen.

All dimensions are in mm ◆ NOT TO SCALE

All dimensions are in mm



The Denham is an electrically operated roller screen. Incorporating a unique suspension system, the unit is suitable for wall, ceiling or specialized mounting. Screens up to 14.6 mtrs (48') are available.

Typical application includes ♦ Cinema Auditoria and Preview Cinemas ♦ Theatres ♦ Conference Center's ♦ Entertainment and Leisure Complexes ♦ Educational Establishments.

General details:

Construction Fabricated lattice framework box contains drive mechanism

Drive Mechanism incorporates separate motor, gear box operating limits and

overrun limit for the raised position.

Fully clad in pre-coated non-reflective black steel panels upon request (POA). Incorporates channel suspension system allowing multi point / angled fixing.

Frame Mounting Ceiling supports

Wall Supports

Barrel / fly bar supports

Screen Roller One piece of aluminium tube for surface rolling / helical wind of Ø3mm wire support

cable.

Surface Options Matt Plus

Matt Preview
Perlux™ 140+
Perlux™ 180+
Spectral 240 3D
High Contrast Grey

Surfaces available in non perforated or perforated form (including mini Perf) Maximum screen width 14.6m (48'). Maximum screen height 2/3 width See below screen surface data information for detailed specifications.

Black edge masking is available.

Operating Supply voltage options 208v 3 phase, 60hZ

400v 3 phase, 50hZ

220v single phase (non standard)

Control Voltage 24v AC

Proprietor: Stage Shop Limited, Registered in England No.4635135, VAT No.810 2744 65.

Speed 42mm/sec (1.6"/sec)

Normal Weight 40kg/mtr of screen width (26.8lb/ft)

Rollsafe® Device Unique dual cable system incorporated in all units for total security

Special Options Multi-Stop

Remote / Radio Control

Roll Down side and top maskings

Control Upper and lower limit switches

3 push – up/down/stop

NOTE: Comprehensive installation instructions accompany screen.

Electrical connections should be completed by an appropriate qualified person.

In the interest of product enhancement, Stage Shop Ltd t/a CAMSTAGE reserve the right to introduce modifications or alterations without notice.